



# PRO BATH CHAIR LIFT™

## SET-UP GUIDE

Pro Bath Chair Lift Parts



1. Power Lifter
2. Mast
3. Upper Mast Extension with Screw and Lock
4. Upper Mast Adjustment Beauty Cover
5. Upper Mast Head Plate
6. Two SNAPTOGGLE® Toggle Bolts for Head Plate
7. Mast Sheave Cover
8. Mast Sheave
9. Mast Sheave Shoulder Bolt
10. Battery
11. Battery Charger
12. Chair
13. Chair Slider
14. Chair Safety Bar

### Tools You Will Need:

- Tape Measure
- 9/16" Open End Wrench
- 2 Allen Wrenches: 3/16" 5/16"
- Adjustable End Wrench up to 1 1/4"
- Hand Drill
- A 1/2" Bit
- Phillips Screwdriver
- Level

### Time You Will Need:

50-60 Minutes

### STEP 1 MEASURE

- A. Bottom of Tub Width - Minimum 18"
- B. Floor to Top of Tub Wall - Maximum 24"
- C. Standard Ceiling Height 90" - 97"  
Exceptions require factory alterations; call 1-800-729-6216
- D. Width of PRO Chair and Lift Mechanism 40" minimum
- E. Clearance Needed OUTWARD from the Front Tub Wall 12"



NOTE: Some installations may require rotating the toilet 45 degrees and refastening it to the floor to gain the space needed for proper operation of the Safe Bathtub Inc Pro Bath Chair Lift™



### STEP 2 ASSEMBLE AND SET UP

1. Measure floor to ceiling & adjust the threaded mast extension to 1" less than the floor to ceiling height; slide on the cover shield.
2. Attach the chair to the slider with the 4 nuts and bolts provided - left or right as needed.



3. Install the mast into the chair slider with the mast sheave toward the tub. Place the mast head plate on top of the mast.
4. Set the power lifter parallel to the front wall of the tub, with the mast stud facing the tub drain. The mast should be at the high end of the tub floor.
5. Set the mast and chair slider on the mast base stud; the chair can rest on the tub wall.
6. Remove the mast sheave and guard, and replace it with the cable installed; **TIGHTEN** the sheave and attach the cable to the chair lift.
7. Extend the mast to touch the ceiling; install the battery; lift the chair into the tub; center the chair on the tub floor.
8. With a level, straighten the mast until it is perpendicular.
9. Check the chair to be sure it is centered in the tub.

# PRO BATH CHAIR LIFT™

## SET UP GUIDE

10. Extend the mast by hand until snug; further tighten 2 revolutions with a 1¼" wrench; tighten down the locking nut.



11. Drill two 1/2" holes through the holes in the mast head plate and install two heavy duty 3/16" SNAPTOGGLE® Toggle Bolts provided. \*See Below



12. Install two stainless screws in the foot plate.
13. Install the safety bar, adjusted for the comfort of the user.

Please direct any questions or inquiries to our Customer Service Department @ 1-800-729-6216

\* Installation Details For The TOGGLER® Brand SNAPTOGGLE® Bolts can be found on the following page. The bolts are available at LOWES®.

(C) 2013 Safe bathtub, Inc., All rights reserved.

All photos and descriptions herein are copyrighted by or under license to Safe Bathtub, Inc., and are not to be reproduced except by written permission.

**TOGGLER**<sup>®</sup> BRAND  
**SNAPTOGGLE**<sup>®</sup>  
3/16" Toggle Bolts




Drill 1/2" diameter hole. Hold metal channel flat alongside plastic straps and slide channel through hole.  
Maximum wall thickness: 3-5/8"  
Minimum clearance behind wall: 1-7/8"



Hold ends of straps between thumb and forefinger and pull toward you until channel rests flush behind wall. Slide plastic cap along straps with other hand until flange of cap is flush with wall.



Snap straps at wall by pushing side to side, snapping off straps level with flange of cap.



Place item over flange. Insert bolt through item and tighten until flush against item, then stop.

For installation tips, technical info & "how to" videos - [www.togglor.com](http://www.togglor.com)  
Para consejos de instalación, información técnica y videos ... [www.togglor.com](http://www.togglor.com)