

ACCESS HATCH IF TOP MOUNT MOTOR

OVERHEAD
96" MINIMUM TYP

TOP
LANDING

LOADING
HEIGHT B
0" MIN
36" MAX

TOTAL TRAVEL =
DISTANCE FROM
BOTTOM LOADING
SILL TO TOP
LOADING SILL

Total
Hoistway
Height

UP TO 4 LANDINGS

FLOOR TO FLOOR
DISTANCE

BOTTOM
LANDING

LOADING
HEIGHT A
24" MIN

ACCESS HATCH

LOADING HEIGHTS ARE FIELD ADJUSTABLE

DO NOT SCALE DRAWING	DRAWN	NAME	DATE	PROJECT NAME
		KSB	2-11-19	PROJECT LOCATION
	PROPRIETARY AND CONFIDENTIAL			COMMENTS: QS200 Generic
	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMERIGLIDE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AMERIGLIDE IS PROHIBITED.			
APPROVAL STATUS:				SIZE DWG. NO.
APPROVED				REV.
APPROVED AS NOTED				
REVISE AND RESUBMIT				SCALE 1:16
SIGNATURE				SHEET 4 OF 4